

MPS 5800

MOBILE PASSENGER STAIRS



CHASSIS

The chassis is produced by steel profiles mounted on a commercial truck according to the customer's demand. The all stairs are stable against wind forces up to 75 km/h.

STAIRWAY

Stairways are provided by telescopic steps. Sidewalls and steps are covered by aluminum and checkered aluminum respectively.

PLATFORM

The platform is produced by steel profiles and its floor is covered by checkered aluminum. Side panels are retractable. The platform and side panels provide bumpers in order to prevent giving any damage to fuselage.

HYDRAULIC SYSTEM

The hydraulic system is provided by an oil tank, a hydraulic pump driven by engine, cylinders used for lifting/telescoping, lock valves, hydraulic valves and some other useful accessories. Emergency hand pump is also used in case of engine failure.

STABILIZERS

The stair is provided by 4 hydraulic stabilizers with lock valves.

SURFACES

The chassis, stairway and platform are custom painted.

ELECTRICAL SYSTEM

The electrical system is powered by a standard battery of the truck. The electrical system is provided by two rear lamps, stair illumination lamps, adjustable headlamp, standard lighting for chassis and a beacon. The all operations are controlled from a control panel.

OPTIONS

1500 mm stair width, canopy, electrical emergency pump, custom painting, logo application, spare wheel.



www.timsan-gse.com

Eyüp Sultan Mh. Kartopu Sk. No.7

Sancaktepe, İstanbul, Turkey

+90 216 527 4270